



FORUM

QUASAR/PROJECTOR PENDANT MOUNT TRIPLE

JOB _____

TYPE _____

FORUM QUASAR/PROJECTOR SERIES

The **QUASAR/PROJECTOR** is a heavy duty, remote ballasted floodlight with a high degree of beam control. The optics are designed to evenly illuminate either vertical or horizontal surfaces.

APPLICATIONS: Classrooms, Office Areas, Libraries, Lobbies, Retail Stores.

MOUNTING: The **QUASAR/PROJECTOR** can be floor, parapet, ceiling, or wall mounted.

SPECIFICATION:

HOUSING: Shall be .125" thick extruded 6063 -T5 aluminum with external surface ribbing for improved heat dissipation which will prolong lamp life. The standard finish for the housing is white. The end plates shall be .375" thick aluminum, gasketed and mechanically attached to the housing. The ends shall be painted white (standard). Custom finishes and bright dip anodize finish available. Consult factory.

LÉNS AND FRAME: Shall be .125" thick high temperature clear patterned tempered glass. The extruded aluminum frame shall be gasketed and secured to the housing by four (4) captive screws. An internal stainless steel wire leader shall be tethered to the frame to facilitate relamping. The frame shall be white (standard).

REFLECTOR: Shall be highly polished, multi-faceted, prefocused anodized aluminum.

REMOTE BALLAST : For lamp wattages from 70-175W, shall be encased and potted, HPS, CWA with a B sound rating. For lamp wattages from 250-400W, shall be encased and potted, HPF, CWA with a C sound rating. All ballasts are provided with an integral wire splice box.

PRODUCT LISTING: Shall be U.L. and C.S.A. listed for Damp Location.

PATENT PENDING: The housing contours of the luminaire constitute a trademark of Forum, Inc.



Quasar/ Projector Series	Type of Ballast 1=Remote Ballast	Voltage 120v 277v	Pendant Mount Triple
QUA	1		PMT
Lamp	Wattage	Shroud Style	Finish
70MH	175PS	NS=No Shroud	WH=White
100MH	250PS	AS=Angle Shroud	CC=Custom
175MH	320PS	RS=Radius Shroud	
250MH	350PS		Options
400MH	400PS		F=Fusing
			WL=With Lamp
			DS=Deflector Shield
			EM-Q=Quartz Restrike
			EM-S=Quartz Socket
			CBB=Cross Blade Baffle
			RBT=Remote Ballast Tray

