



FORUM

QUASAR/PROJECTOR

INVERTED SHROUD

JOB _____

TYPE _____

FORUM QUASAR/PROJECTOR SERIES

The **QUASAR/PROJECTOR** is a heavy duty, remote ballasted floodlight with a high degree of beam control. The optics are designed to evenly illuminate either vertical or horizontal surfaces.

APPLICATIONS: Cafeterias, Open Offices, Conference Centers, Lecture Halls, Auditoriums, Churches, Gymnasiums and Natatoriums.

MOUNTING HEIGHT: Distance from the ceiling to the top of the fixture can be a minimum of 18".

SPECIFICATION:

FIXTURE BODY: Shall be .125" thick extruded 6063 -T5 aluminum with external surface ribbing for improved heat dissipation which will prolong lamp life. The standard finish for the housing is white. The end plates shall be .375" thick aluminum, gasketed and mechanically attached to the housing. The ends shall be painted white (standard).

LENS AND FRAME: Shall be .125" thick high temperature clear patterned tempered glass. The extruded aluminum frame shall be gasketed and secured to the housing by four (4) captive screws. The frame shall be white (standard).

REFLECTOR: Shall be highly polished, multi-faceted prefocused anodized aluminum.

SHROUD: Shall be fabricated from 18 gauge steel. The shroud shall be die formed, welded, and ground smooth to provide a seamless finished appearance. Standard finish shall be white. Custom finishes available.

MOUNTING YOKE: Shall be die formed from 12 gauge C.R.S. with provision for mounting to and covering a 4 1/2" octagon box.

WALL MOUNTING BRACKET: Shall be die formed from 18 gauge C.R.S.. Standard finish is white.

BALLAST HOUSING: Shall be .090" thick 6061-T5 aluminum with a white painted finish.

BALLAST: For lamp wattages from 70-175W, shall be integrally mounted, encased and potted, HPF, CWA with a B sound rating. The ballast shall be integrally mounted core and coil, HPF, CWA and thermally protected for lamp wattages from 250-400W.

PRODUCT LISTING: Shall be U.L. and C.S.A. listed

PATENT PENDING: The housing contours of the luminaire constitute a trademark of Forum, Inc.

