




R4AU-05-O (265 MA, T-8)
R4AU-10-O (430 MA, T-12)

DESCRIPTION: The **FORUM/ROUND** fixture provides an indirect general illumination where quality lighting is required to meet specific tasks.

APPLICATIONS: Classrooms, Office Areas, Libraries, Lobbies, Retail Stores, Design Centers.

MOUNTING HEIGHTS: The top of the fixture to ceiling should be a minimum of 18" for all fixtures (see mounting sheet for detail information).



LIGHT LENGTH	O.A. FIXTURE LENGTH			ADD FOR 800 MA	STEM/CABLE	LAMPS REQUIRED			INPUT WATTS		
	EDGE	SPAN	HANG			265 MA	430 MA	800 MA	265 MA	430 MA	800 MA
2 FT	2'-1/2"	3'	2'-4 1/2"	N/A	2/0	1-F017	1-F20	N/A	25	26	N/A
3 FT	3'-1/2"	4'	3'-4 1/2"	-	2/0	1-F025	1-F30	-	30	48	-
4 FT	4'-1/2"	5'	4'-4 1/2"	-	2/0	1-F032	1-F40	-	37	52	-
6 FT	6'-1/2"	7'	6'-4 1/2"	-	2/0	2-F025	2-F30	-	58	76	-
8 FT	8'-1/2"	9'	8'-4 1/2"	-	2/0	2-F032	2-F40	-	70	92	-
12 FT	12'-1/2"	13'	12'-4 1/2"	-	2/0	3-F032	3-F40	-	107	144	-
16 FT	16'-1/2"	17'	16'-4 1/2"	-	2/0	4-F032	4-F40	-	140	184	-
18 FT	18'-1/2"	19'	18'-6 5/8"	-	2/1	6-F025	6-F30	-	174	228	-
20 FT	20'-1/2"	21'	20'-6 5/8"	-	2/1	4-F025/2-F032	4-F30/2-F40	-	177	236	-
22 FT	22'-1/2"	23'	22'-6 5/8"	-	2/1	2-F025/4-F032	2-F30/4-F40	-	198	260	-
24 FT	24'-1/2"	25'	24'-6 5/8"	-	2/1	6-F032	6-F40	-	210	276	-
28 FT	28'-1/2"	29'	28'-6 5/8"	-	2/1	4-F025/4-F032	4-F30/4-F40	-	247	328	-
32 FT	32'-1/2"	33'	32'-6 5/8"	-	2/1	8-F032	8-F40	-	280	368	-
36 FT	36'-1/2"	37'	36'-8 3/4"	N/A	2/2	9-F032	9-F40	N/A	317	420	N/A

SPECIFICATION:

The **FORUM/ROUND** housing shall be 4" in diameter constructed of .125" aluminum extrusion 6063-T5 alloy for structural rigidity. Sockets shall be prewired and factory installed. The ends shall be .250" thick aluminum with no visible fasteners. Standard continuous single sections shall be 16 feet. Standard finish shall be white consisting of a high solids baked polyester paint pretreated with a five (5) stage cleaning/conversion coating rust inhibitor. Other painted architectural finishes available as well as satin anodized.

REFLECTOR: Reflector shall be die formed 22 gauge aluminum with 86% reflectivity.


LENS: Optional, shall be clear acrylic prismatic with 20% DR for optical control.

BALLAST: Ballast shall be energy saving CBM/ETL certified Class P.

PRODUCT LISTING: Shall be U.L. listed.


CANDLEPOWER SUMMARY

CATALOG NO.: R4AU-05-O
LAMP TYPE: F32T8/SP35/RS
LUMENS: 2900
FIXTURE EFFICIENCY: 83.0%
LUMINAIRE INPUT WATTS: 37
TEST REPORT NO.: B.A.L. 7693.0



ANGLE	CANDELA	LUMENS
180	729	
175	735	70
165	749	209
155	700	315
145	668	399
135	588	414
125	490	387
115	388	328
105	240	211
95	94	73
90	44	
85	6	2
75	0	0
65	0	0
55	0	0
45	0	0
35	0	0
25	0	0
15	0	0
5	0	0
0	0	

CATALOG NO.: R4AU-10-O
LAMP TYPE: F40T12/WW/RS
LUMENS: 3200
FIXTURE EFFICIENCY: 76.7%
LUMINAIRE INPUT WATTS: 53
TEST REPORT NO.: B.A.L. 7694.0



ANGLE	CANDELA	LUMENS
180	736	
175	742	71
165	740	208
155	686	309
145	651	391
135	568	402
125	477	375
115	383	318
105	276	222
95	166	112
90	126	
85	79	41
75	16	5
65	0	0
55	0	0
45	0	0
35	0	0
25	0	0
15	0	0
5	0	0
0	0	