




R6AUT-0505-L (265 MA, T-8)
R6AUT-2020-L (430 MA, T-12)

DESCRIPTION: The FORUM/ROUND fixture provides an indirect general illumination where quality lighting is required to meet specific tasks.

APPLICATIONS: Classrooms, Office Areas, Libraries, Lobbies, Retail Stores, Design Centers.

MOUNTING HEIGHTS: The top of the fixture to ceiling should be a minimum of 18" for all fixtures (see mounting sheet for detail information).



LIGHT LENGTH	O.A. FIXTURE LENGTH			ADD FOR 800 MA	STEM/ CABLE	LAMPS REQUIRED			INPUT WATTS		
	EDGE	SPAN	HANG			265 MA	430 MA	800 MA	265 MA	430 MA	800 MA
2 FT	2'-1/2"	3'	2'-4 1/2"	N/A	2/0	2-F017	2-F20	N/A	47	43	N/A
3 FT	3'-1/2"	4'	3'-4 1/2"	-	2/0	2-F025	2-F30	-	58	76	-
4 FT	4'-1/2"	5'	4'-4 1/2"	-	2/0	2-F032	2-F40	-	70	92	-
6 FT	6'-1/2"	7'	6'-4 1/2"	-	2/0	4-F025	4-F30	-	116	152	-
8 FT	8'-1/2"	9'	8'-4 1/2"	-	2/0	4-F032	4-F40	-	140	184	-
12 FT	12'-1/2"	13'	12'-4 1/2"	-	2/0	6-F032	6-F40	-	210	276	-
16 FT	16'-1/2"	17'	16'-4 1/2"	-	2/0	8-F032	8-F40	-	280	368	-
18 FT	18'-1/2"	19'	18'-6 5/8"	-	2/1	12-F025	12-F30	-	348	456	-
20 FT	20'-1/2"	21'	20'-6 5/8"	-	2/1	8-F025/4-F032	8-F30/4-F40	-	350	460	-
22 FT	22'-1/2"	23'	22'-6 5/8"	-	2/1	4-F025/8-F032	4-F30/8-F40	-	396	520	-
24 FT	24'-1/2"	25'	24'-6 5/8"	-	2/1	12-F032	12-F40	-	420	552	-
28 FT	28'-1/2"	29'	28'-6 5/8"	-	2/1	8-F025/8-F032	8-F30/8-F40	-	490	644	-
32 FT	32'-1/2"	33'	32'-6 5/8"	-	2/1	16-F032	16-F40	-	560	736	-
36 FT	36'-1/2"	37'	36'-8 3/4"	N/A	2/2	18-F032	18-F40	N/A	630	828	N/A

SPECIFICATION:

The FORUM/ROUND housing shall be 6" in diameter constructed of .125" aluminum extrusion 6063-T5 alloy for structural rigidity. Sockets shall be prewired and factory installed. The ends shall be .250" thick aluminum with no visible fasteners. Standard continuous single sections shall be 16 feet. Standard finish shall be white consisting of a high solids baked polyester paint pretreated with a five (5) stage cleaning/conversion coating rust inhibitor. Other painted architectural finishes available as well as satin anodized. This extrusion will accommodate a track lighting system. Consult factory for compatibility.

REFLECTOR: Reflector shall be die formed 22 gauge aluminum with 86% reflectivity.

LENS: Shall be clear acrylic prismatic with 20% DR for optical control.

BALLAST: Ballast shall be energy saving CBM/ETL certified Class P.

PRODUCT LISTING: Shall be U.L. listed.

CANDLEPOWER SUMMARY

CATALOG NO.: R6AUT-0505-L
LAMP TYPE: F32T8/SP35/RS
LUMENS: 2900
FIXTURE EFFICIENCY: 62.3%
LUMINAIRE INPUT WATTS: 69
TEST REPORT NO.: B.A.L. 4943.0

CATALOG NO.: R6AUT-2020-L
LAMP TYPE: F40T12WW/RS
LUMENS: 3200
FIXTURE EFFICIENCY: 59.7%
LUMINAIRE INPUT WATTS: 84
TEST REPORT NO.: B.A.L. 4945.0

