

Customer Name	Date
Project Name	
Catalog Number	

# Frame Series

## Vertical Mount

The **Frame series by Forum** combines fundamental design form with the latest cutting edge LED technology to create a minimalistic statement. Available in several standard portal configurations, Frame's directional light source placement can be customized to fit each application. Frame offers multiple mounting configurations with a standard cordless power system.

### Ordering

FRM			LED		SHIELDING		MOUNTING		VOLTAGE		FINISH		OPTION 1		OPTION 2	
ORIENTATION	SIZE	DIRECTION	lm/ft	CCT	WOL	C	120V	WH	EC	90 CRI						
<b>V</b> Vertical  <small>*For horizontal orientation see horizontal sheet</small>	<b>2</b> 26" square	<b>I</b> Inside	<b>11</b> 110 lm/ft	<b>27</b> 2700k temp	White Opal Lens	<b>C</b> Cable	<b>277V</b>	<b>SV</b> Silver	<b>EC</b> Emergency Circuit	<b>90 CRI</b> 90 CRI						
			<b>3</b> 38" square	<b>O</b> Outside							<b>DIMMING OPTIONS (CHOOSE 1)</b>					
	<b>4</b> 50" square	<b>U</b> Up <small>* Not available in surface mount</small>									<b>55</b> 550 lm/ft	<b>30</b> 3000k temp	<b>D10V</b> 0-10V dimming 1% power class	<b>DLA2</b> Lutron Hi-lume 1% 2-wire LED driver (120V forward phase only)		
											<b>D</b> Down	<b>35</b> 3500k temp	<b>40</b> 4000k temp	<b>DLEH5</b> Lutron Hi-lume 1%-H EcoSystem LED driver with soft-On, Fade-to-Black	<b>DLE55</b> Lutron 5-Series EcoSystem LED driver	
												<b>50</b> 5000k temp	<b>DALI</b> Digitally Addressable Lighting Interface	<b>DIM</b> Dimming  Please specify dimming manufacturer/model (if required)		

- 1 60 option available with 40 Fixture Length only
- 2 90 option available with 60 Fixture Length only
- 3 A2 option available with 80 Fixture Length only
- 4 10ft aircraft cables with gripples and hourglass sleeves pre-installed. Canopy kits ordered separately
- 5 G2 option available with 60 Fixture Length and 90 Lumen Output options only
- 6 10ft Power Cord included. 300V 18AWG, 5-Conductor wire
- 7 Powercord not required for G2 mounting option



Customer Name	Date
Project Name	
Catalog Number	

## CONTROLS & SENSORS

Ordering Code	Description

## DIMMING OPTIONS

Ordering Code	Description
D10V	0-10V Dimming, 1% power class
DLA2	Lutron Hi-lume 1% 2-1ire LED driver (120V forward phase only)
DLEH5	Lutron Hi-lume 1% H EcoSystem LED driver with soft-On, Fade-to-Black
DLE55	Lutron 5-Series EcoSystem LED driver
DALI	Digitally Addressable Lighting Interface
DIM	Custom Dimming. Please specify dimming manufacturer/model

## LUMEN MULTIPLICATION TABLE

Ordering Code	Description

















## LUMENS PER FIXTURE

FRAME	@ 110LM / FT	@ 550LM / FT
2'	880	4400
3'	1320	6600
4'	1760	8800



Customer Name	Date
Project Name	
Catalog Number	

## Light Source Configurations

<b>C CABLE</b>	<b>H STEM</b>	<b>W STANDOFF</b>	<b>S SURFACE</b>
I - Inside 	I - Inside 	I - Inside 	I - Inside 
O - Outside 	O - Outside 	O - Outside 	O - Outside 
R - Room 	R - Room 	R - Room 	R - Room 
W - Wall 	W - Wall 	W - Wall 	Option Unavailable 



# Frame Series

Vertical Mount



Customer Name	Date
Project Name	
Catalog Number	

## CONSTRUCTION

<b>Housing:</b>	Extruded aluminum, machined endcaps
<b>Lens:</b>	White opal lenses
<b>Optical Assembly:</b>	.040" aluminum in a pre-paint white finish. Fully wired unit remains completely accessible from below via ballast panel.
<b>Paint:</b>	Black, White, Silver, Custom Color
<b>Weight:</b>	

## OPTICAL SYSTEM

<b>Lumens:</b>	110 - 550 lm/ft
<b>Distribution:</b>	Direct lambertian. Multiple directional configurations available
<b>Efficacy:</b>	
<b>Wattage:</b>	16 - 120 watts/ft
<b>CCT:</b>	2700k, 3000K, 3500K, 4000K, 5000K
<b>CRI (Min):</b>	90CRI
<b>R9 (Min):</b>	
<b>Color Consistency:</b>	
<b>Luminance Uniformity:</b>	

## ELECTRICAL

<b>Input Voltage:</b>	120V, 277V, Universal Voltage
<b>Input Frequency:</b>	50/60Hz
<b>Power Factor (PF):</b>	
<b>Total Harmonic Distortion (THD):</b>	
<b>Thermal Protection:</b>	
<b>Temperature / Humidity:</b>	
<b>Transient Protection:</b>	
<b>Electronic Vibration Testing:</b>	

## CONTROLS

<b>Dimming:</b>	0-10V 1% power class; Lutron Hi-lume 1% 2-wire LED driver; Lutron Hi-lume 1% EcoSystem LED driver with soft-On Fade-to-Black; Lutron 5-Series EcoSystem LED driver; Digitally Addressable Lighting Interface; Custom Dimming
-----------------	--

## AMBIENT TEMPERATURE

Product ID	Operating Temperature
Frame Series	

## LUMEN MAINTENANCE

Projected L85 per IES TM-21 at max 35°C

<b>50,000 HR</b>
------------------

## MOUNTING

- C - Cable
- S - Rigid Surface
- H - Stem
- W - Stand Off

For Product or Technical Questions:

E: [INFO@FORUMLIGHTING.COM](mailto:INFO@FORUMLIGHTING.COM)  
T: +1 412 781 5970



[forumlighting.com](http://forumlighting.com) | [gecurrent.com](http://gecurrent.com)

© 2021 Current Lighting Solutions, LLC. All rights reserved. GE and the GE monogram are trademarks of the General Electric Company and are used under license. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.  
IND737 | (Rev 11/30/21)