



Frame Series

Horizontal Mount

The Frame series by Forum combines fundamental design form with the latest cutting edge LED technology to create a minimalistic statement. Available in several standard portal configurations, Frame's directional light source placement can be customized to fit each application. Frame offers multiple mounting configurations with a standard cordless power system.

Ordering

FRM			LED		SHIELDING		MOUNTING		VOLTAGE		FINISH		OPTION 1		OPTION 2	
ORIENTATION	SIZE	DIRECTION	lm/ft	CCT	WOL	CC										
H Horizontal *For vertical orientation see vertical sheet	2 26" square	I Inside	11 110 lm/ft	27 2700k temp	White Opal Lens	CC Conical Cable	120V	WH White	EC Emergency Circuit	90 CRI 90 CRI						
	3 38" square	O Outside	55 550 lm/ft	30 3000k temp		C Cable	277V	SV Silver	DIMMING OPTIONS (CHOOSE 1)							
	4 50" square	U Up * Not available in surface mount		35 3500k temp		UNV Universal	BK Black	D10V 0-10V dimming 1% power class	DLA2 Lutron Hi-lume 1% 2-wire LED driver (120V forward phase only)							
				40 4000k temp				CC Custom Color	DLEH5 Lutron Hi-lume 1%-H EcoSystem LED driver with soft-On, Fade-to-Black	DLE55 Lutron 5-Series EcoSystem LED driver						
				50 5000k temp				Provide custom color RAL#:	DALI Digitally Addressable Lighting Interface	DIM Dimming						
		D Down														

- 1 60 option available with 40 Fixture Length only
- 2 90 option available with 60 Fixture Length only
- 3 A2 option available with 80 Fixture Length only
- 4 10ft aircraft cables with gripples and hourglass sleeves pre-installed. Canopy kits ordered separately
- 5 G2 option available with 60 Fixture Length and 90 Lumen Output options only
- 6 10ft Power Cord included. 300V 18AWG, 5-Conductor wire
- 7 Powercord not required for G2 mounting option



Frame Series

Horizontal Mount

Customer Name	Date
Project Name	
Catalog Number	

CONTROLS & SENSORS

Ordering Code	Description
C110	Casambi (1x 010v)
C210	Casambi (2x 010v)

LUMENS PER FIXTURE

FRAME	@ 110LM / FT	@ 550LM / FT
2'	880	4400
3'	1320	6600
4'	1760	8800





















DIMMING OPTIONS

Ordering Code	Description
D10V	0-10V Dimming, 1% power class
DLA2	Lutron Hi-lume 1% 2-1ire LED driver (120V forward phase only)
DLEH5	Lutron Hi-lume 1% H EcoSystem LED driver with soft-On, Fade-to-Black
DLE55	Lutron 5-Series EcoSystem LED driver
DALI	Digitally Addressable Lighting Interface
DIM	Custom Dimming. Please specify dimming manufacturer/model



Customer Name	Date
Project Name	
Catalog Number	

Light Source Configurations

CC CONICAL CABLE	C CABLE	H STEM	W STANDOFF	S SURFACE
I - Inside 	I - Inside 	I - Inside 	I - Inside 	I - Inside 
O - Outside 	O - Outside 	O - Outside 	O - Outside 	O - Outside 
D - Down 	D - Down 	D - Down 	D - Down 	D - Down 
U - Up 	U - Up 	U - Up 	U - Up 	Option Unavailable 




Customer Name	Date
Project Name	
Catalog Number	

Photometrics

Logic/Config
Frame H

8,889 Lumens

FRM-H-4-O-55LED40-WOL-C-WH



Maximum Candela = 1117.3 Located At Horizontal Angle = 45, Vertical Angle = 85
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180)
 # 2 - Vertical Plane Through Horizontal Angles (65 - 225)
 # 3 - Vertical Plane Through Horizontal Angles (90 - 270)

ZONE	LUMENS	% OF FIXTURE
0-20	15.25	0.20
0-30	102.35	1.20
0-40	331.38	3.70
0-60	1406.86	15.80
0-80	3312.23	37.30
0-90	4446.43	50.00

ZONE	LUMENS	% OF FIXTURE
10-90	4446.08	50.00
20-40	316.13	3.60
20-50	742.65	8.40
40-70	1943.36	21.90
60-80	1905.37	21.40
70-80	1037.49	11.70
80-90	1134.2	12.80
90-110	2171.66	24.40
90-120	3039.52	34.20
90-130	3689.95	41.50
90-150	4342.19	48.80
90-180	4442.75	50.00
110-180	2271.09	25.50
0-180	8889.18	100.00



Customer Name	Date
Project Name	
Catalog Number	

CONSTRUCTION

Housing:	Extruded aluminum, machined endcaps
Lens:	White opal lenses
Optical Assembly:	.040" aluminum in a pre-paint white finish. Fully wired unit remains completely accessible from below via ballast panel.
Paint:	Black, White, Silver, Custom Color

OPTICAL SYSTEM

Lumens:	110 - 550 lm/ft
Distribution:	Direct lambertian. Multiple directional configurations available
Efficacy:	Up to 126 LPW
Wattage:	16 - 120 watts/ft
CCT:	2700k, 3000K, 3500K, 4000K, 5000K
CRI (Min):	90CRI
R9 (Min):	65
Color Consistency:	2SDCM

ELECTRICAL

Input Voltage:	120V, 277V, Universal Voltage
Input Frequency:	50/60Hz
Power Factor (PF):	>0.9
Total Harmonic Distortion (THD):	<16% - 120V <20% - 277V
Temperature / Humidity:	Suitable for Damp Locations
Transient Protection:	All Non-Lutron = 2.5KV Lutron = 4KV

CONTROLS

Dimming:	0-10V 1% power class; Lutron Hi-lume 1% 2-wire LED driver; Lutron Hi-lume 1% EcoSystem LED driver with soft-On Fade-to-Black; Lutron 5-Series EcoSystem LED driver; Digitally Addressable Lighting Interface; Custom Dimming C110 Casambi (1x 010v) C210 Casambi (2x 010v)
-----------------	--

LUMEN MAINTENANCE

- L70>50K Hours

MOUNTING

- CC - Conical Cable
- C - Cable
- S - Rigid Surface
- H - Stem
- W - Stand Off

DESIGN LIFE & WARRANTY

- Warranty:**
- LED boards - 5 years
 - LED drivers (standard) - 5 years
 - LED drivers (Lutron) - 3 years

For Product or Technical Questions:

E: INFO@FORUMLIGHTING.COM
T: +1 412 781 5970