



Customer Name	Date
Project Name	
Catalog Number	

Frame Series

Vertical Mount

The **Frame series by Forum** combines fundamental design form with the latest cutting edge LED technology to create a minimalistic statement. Available in several standard portal configurations, Frame's directional light source placement can be customized to fit each application. Frame offers multiple mounting configurations with a standard cordless power system.

Ordering

FRM			LED		SHIELDING		MOUNTING		VOLTAGE		FINISH		OPTION 1		OPTION 2	
ORIENTATION	SIZE	DIRECTION	lm/ft	CCT	WOL	C	120V	WH	EC	90 CRI						
V Vertical <small>*For horizontal orientation see horizontal sheet</small>	2 26" square	I Inside	11 110 lm/ft	27 2700k temp	White Opal Lens	C Cable	277V	SV Silver	DIMMING OPTIONS (CHOOSE 1)							
			4 50" square	U Up <small>* Not available in surface mount</small>					D Down	55 550 lm/ft	30 3000k temp	UNV Universal	BK Black	D10V 0-10V dimming 1% power class	DLA2 Lutron Hi-lume 1% 2-wire LED driver (120V forward phase only)	
	DLEH5 Lutron Hi-lume 1%-H EcoSystem LED driver with soft-On, Fade-to-Black	DLE55 Lutron 5-Series EcoSystem LED driver														
	DALI Digitally Addressable Lighting Interface	DIM Dimming Please specify dimming manufacturer/model (if required)														
				40 4000k temp												
			50 5000k temp													

- 1** 60 option available with 40 Fixture Length only
- 2** 90 option available with 60 Fixture Length only
- 3** A2 option available with 80 Fixture Length only
- 4** 10ft aircraft cables with gripples and hourglass sleeves pre-installed. Canopy kits ordered separately
- 5** G2 option available with 60 Fixture Length and 90 Lumen Output options only
- 6** 10ft Power Cord included. 300V 18AWG, 5-Conductor wire
- 7** Powercord not required for G2 mounting option



Customer Name	Date
Project Name	
Catalog Number	

CONTROLS & SENSORS

Ordering Code	Description
C110	Casambi (1x 010v)
C210	Casambi (2x 010v)

LUMENS PER FIXTURE

FRAME	@ 110LM / FT	@ 550LM / FT
2'	880	4400
3'	1320	6600
4'	1760	8800

DIMMING OPTIONS

Ordering Code	Description
D10V	0-10V Dimming, 1% power class
DLA2	Lutron Hi-lume 1% 2-1ire LED driver (120V forward phase only)
DLEH5	Lutron Hi-lume 1% H EcoSystem LED driver with soft-On, Fade-to-Black
DLE55	Lutron 5-Series EcoSystem LED driver
DALI	Digitally Addressable Lighting Interface
DIM	Custom Dimming. Please specify dimming manufacturer/model



Customer Name	Date
Project Name	
Catalog Number	

Light Source Configurations

C CABLE	H STEM	W STANDOFF	S SURFACE
I - Inside 	I - Inside 	I - Inside 	I - Inside
O - Outside 	O - Outside 	O - Outside 	O - Outside
R - Room 	R - Room 	R - Room 	R - Room
W - Wall 	W - Wall 	W - Wall 	Option Unavailable



Frame Series

Vertical Mount

Customer Name	Date
Project Name	
Catalog Number	

CONSTRUCTION

Housing:	Extruded aluminum, machined endcaps
Lens:	White opal lenses
Optical Assembly:	.040" aluminum in a pre-paint white finish. Fully wired unit remains completely accessible from below via ballast panel.
Paint:	Black, White, Silver, Custom Color

OPTICAL SYSTEM

Lumens:	110 - 550 lm/ft
Distribution:	Direct lambertian. Multiple directional configurations available
Efficacy:	Up to 124 LPW
Wattage:	16 - 120 watts/ft
CCT:	2700k, 3000K, 3500K, 4000K, 5000K
CRI (Min):	90CRI
R9 (Min):	65
Color Consistency:	2SDCM

ELECTRICAL

Input Voltage:	120V, 277V, Universal Voltage
Input Frequency:	50/60Hz
Power Factor (PF):	>0.9
Total Harmonic Distortion (THD):	<16% - 120V <20% - 277V
Temperature / Humidity:	Suitable for Damp Locations
Transient Protection:	All Non-Lutron = 2.5KV Lutron = 4KV

CONTROLS

Dimming:	0-10V 1% power class; Lutron Hi-lume 1% 2-wire LED driver; Lutron Hi-lume 1% EcoSystem LED driver with soft-On Fade-to-Black; Lutron 5-Series EcoSystem LED driver; Digitally Addressable Lighting Interface; Custom Dimming C110 Casambi (1x 010v) C210 Casambi (2x 010v)
-----------------	---

LUMEN MAINTENANCE

- L70>50K Hours

MOUNTING

- C - Cable
- S - Rigid Surface
- H - Stem
- W - Stand Off

DESIGN LIFE & WARRANTY

- Warranty:**
- LED boards - 5 years
 - LED drivers (standard) - 5 years
 - LED drivers (Lutron) - 3 years

For Product or Technical Questions:

E: INFO@FORUMLIGHTING.COM
T: +1 412 781 5970